

## Flat Panel Ceiling Lifts—FPLCV2SLIM +R+TILT

The FPLCV2+R popular series of flat panel ceiling lifts with full rotation, can be also equipped with flat panel tilt ability, up to 30degrees!

This optimum solution, provides maximum utility with its full rotation and best viewing angle for different positions in the same room. For example, viewing from table top or from bed or sofa demands different viewing angles. This is easily solved by the variety of viewing angles that FPLCV2+R+TILT series offers to the end user!



| Model  | FPLC V2 Slim 30-40+R+TILT                          | FPLC V2 Slim 42-50+R+TILT | FPLC V2 Slim 52-60+R+TILT+LOCK |
|--|--|---------------------------|--------------------------------|
| Maximum flat panel dimensions (WxHxD)          | ≤ 1125x620x90mm                                    | ≤ 1280x755x90mm           | ≤ 1480x900x90mm                |
| Maximum load (flat panel+ceiling cover)        | 25kg   | 30kg                      | 35kg                           |
| Lift dimensions (WxHxD), excluding control box | 1330x220x1025mm                                    | 1615x220x1250mm           | 1820x250x1525mm                |
| Swiveling angle                                | 90degrees  |                           |                                |
| Rotation ability (CW & CCW)                    | ±180degrees both ways : 180° CW & 180° CCW         |                           |                                |
| Flat panel electric tilt ability               | up to 30degrees                                    |                           |                                |
| Mounting flat panel holes pattern up to        | 600x400mm  | 800x400mm                 | 800x600mm                      |
| Standard color of metallic parts               | powder coating in RAL 9005 black or RAL 9016 white |                           |                                |
| Power supply                                   | 110-230VAC-50/60Hz                                 |                           |                                |
| Standard control option                        | dry contacts control box                           |                           |                                |
| Optional controls                              | RF or IR remote control, RS 232 or 485 ports       |                           |                                |

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS

All above information may change by the manufacturer without prior notice or obligation of any kind.