

## Flat Panel Ceiling Lifts—FPLCV2SLIM +R

FPLC V2 Slim+R series of flat panel ceiling lift mechanisms completes the series of elegant and slim ceiling mechanism with new models that comprise rotation ability and excellent utility!

Giving ideal solutions in most demanding applications of reduce space, (e.g. marine or vessel applications), FPLC V2 Slim+R series impress both users and integrators!

FPLC V2 Slim+R models provide swiveling at 90 degrees from ceiling and rotation ability up to  $\pm 180$ degrees (full rotation to both directions).

The model suitable for flat panels up to 60"-65" is also equipped with an electric safety locking system in closed position, to ensure maximum security of application.



Model	FPLCV2Slim30-40 +R	FPLCV2Slim42-50 +R	FPLCV2Slim52-60 +R+LOCK
Maximum flat panel dimensions (WxHxD)	$\leq 1025 \times 620 \times 90$ mm	$\leq 1280 \times 755 \times 90$ mm	$\leq 1480 \times 900 \times 90$ mm
Maximum load (flat panel+ceiling cover)	25kg	30kg	35kg
Lift dimensions (WxHxD) excluding control box	1330x220x1125mm	1613x220x1300mm	1820x220x1525mm
Maximum swiveling angle	90degrees		
Rotation ability (CW & CCW)	$\pm 180$ degrees both ways : 180° CW & 180° CCW		
Mounting flat panel holes pattern up to	600x400mm	800x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white		
Power supply	110-230VAC-50/60Hz		
Standard control option	dry contacts control box		
Optional controls	RF or IR remote control, RS 232 or 485 ports		

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS  
All above information may change by the manufacturer without prior notice or obligation of any kind.